



SPC HYBRID FLOORING

www.auslayindustries.com.au

Stone Plastic Composite Rigid Core Click Plank Flooring known as hybrid flooring

DURA*7 - “IXPE BACK PADDING FITTED VERSION”

INTERNAL FLOORS - direct float over most substrates

Description -

7mm total thickness / 0.5mm wear layer / 1.5mm IXPE

SPC Hybrid Flooring is a very durable, waterproof click plank float flooring for both commercial and residential installations. Dura Collection “IXPE back padding fitted version” lets you float install directly over most prepared substrates without the need for an underlayment. The 1.5mm IXPE back pad gives you an acoustic, cushioned, moisture resistant backing, allowing for a fast and easy install. For that extra acoustic reduction float install over our Insulayment or Quietwalk Plus Underlayment. Realistic looking timber grain textures and 4 new bold colours.



No. 19D Barnwood
No. 20D Regional Oak
No. 22D Argentine Oak

Features

- 1.5mm IXPE back pad
- 0.5mm wear layer
- 100% waterproof
- Scratch resistant
- Stain resistant
- 100% Phthalate free
- 100% VOC free
- Zero expansion
- Zero shrinkage
- Easy to install
- Slip Rated : P4
- Very durable
- Pet friendly
- Realistic timber looks
- 3 Bold new colours
- Internal floors
- Direct float install
- Heavy Residential
- Heavy commercial
- Easy to keep clean
- DIY or professional
- dB Acoustic reduction
- Float install over our eco friendly underlayments
- Direct float install over prepared substrates
- Moisture resistant back padding
- Acoustic reducing IXPE back padding
- Cushioned feel

Specifications

- Plank Size : 1220mm x 178mm
- Thickness : 7.0mm total, 5mm core + 0.5mm wear layer
- Plus 1.5mm IXPE back padding fitted
- 10 planks per box packaged
- 2.17 m2 per box packaged
- Vantage 2G click lock system
- 25 year residential warranty
- 10 year commercial warranty
- Do not exceed 200kg weight loading

Recommended Substrates

- Cured concrete / Masonry surfaces / Block
- Plywood / Particle board flooring
- Compressed fibre cement
- Wood floor / timber
- Existing Floor coverings (tiles, vinyl, cork, timber)
- Hebel flooring
- Substrate preparation is required
- Substrate deflection cannot exceed L/360
- Do not install over carpet

1.5mm IXPE Back Padding Fitted
DIRECT FLOAT INSTALL OVER MOST SUBSTRATES
FLOAT INSTALL OVER UNDERLAYMENTS



SPC HYBRID FLOORING

www.auslayindustries.com.au

Stone Plastic Composite Rigid Core Click Plank Flooring known as hybrid flooring

DURA*7 - "IXPE BACK PADDING FITTED VERSION"



- No. 19D Barnwood
- No. 20D Regional Oak
- No. 21D S. Blackbutt
- No. 22D Argentine oak

DURA HYBRID WITH IXPE BACK PADDING

Colour Chart

3 new bold colours

