

# SPC HYBRID FLOORING

www.auslayindustries.com.au

Stone Plastic Composite Rigid Core Click Plank Flooring known as hybrid flooring

CASA - "IXPE BACK PADDING FITTED VERSION"

# **INTERNAL FLOORS - direct float over most substrates**

### Description

SPC Hybrid Flooring is a very durable, waterproof click plank float flooring for residential installations. Casa series " IXPE back padding fitted version" lets you float install directly over most prepared substrates without the need for an underlayment. The 1.5mm IXPE back pad gives you an acoustic, cushioned, moisture resistant backing, allowing for a fast and easy install. For that extra acoustic reduction float install over our Insulayment or Quietwalk Plus Underlayment. Realistic looking timber grain textures and 6 new bold colours.

#### **Features**

- 1.5mm IXPE back pad
- **Eco Friendly**
- 100% waterproof
- Scratch resistant
- Stain resistant
- 100% Phthalate free
- 100% VOC free
- Zero expansion
- Zero shrinkage
- Easy to install

#### **Specifications**

- Plank Size : 1220mm x 178mm
- Thickness : 5.8mm total, 4mm core + 0.3mm wear layer
- Plus 1.5mm IXPE back padding fitted
- 12 planks per box packaged
- 2.61 m2 per box packaged
- Vantage 2G click lock system
- 15 year residential warranty
- Do not exceed 200kg weight loading

- Very durable
- Pet friendly
- Realistic timber looks
- 8 Bold new colours •
  - Direct float install
- Heavy Residential
- Easy to keep clean
- **DIY** or professional



No. 8B	Hessian
No.10B	Ash
No.11B	Canyon
No.12B	Bark
No.17B	Sawn oak
No.18B	Fossil Wood

- Float install over our eco friendly underlayments
- Direct float install over prepared substrates .
- Moisture resistant back padding
- Acoustic reducing IXPE back padding
- Cushioned feel

## **1.5mm IXPE Back Padding Fitted**

### DIRECT FLOAT INSTALL OVER MOST SUBSTRATES

#### **Recommended Substrates**

- Cured concrete / Masonry surfaces / Block
- Plywood / Particle board flooring
- Compressed fibre cement •
- Wood floor / timber •
- Existing Floor coverings (tiles, vinyl, cork, timber) •
- Hebel flooring •
- Substrate preparation is required
- Substrate deflection cannot exceed L/360
- Do not install over carpet

.

•

- Internal floors

- .



# **SPC HYBRID FLOORING**

www.auslayindustries.com.au

Stone Plastic Composite Rigid Core Click Plank Flooring known as hybrid flooring

CASA - "IXPE BACK PADDING FITTED VERSION"



No. 8B Hessian No.10B Ash No.11B Canyon No.12B Bark No.17B Sawn oak No.18B Fossil Wood

## CASA HYBRID WITH IXPE BACK PADDING

**Colour Chart** 

6 new bold colours











